

# Kassbohrer

Semi-lowbed trailer / ext. 15.2 m + 2 steering  
axles

## GENERAL

|                         |                                                         |
|-------------------------|---------------------------------------------------------|
| ID number               | 0062336                                                 |
| Brand                   | Kassbohrer                                              |
| Type                    | Semi-lowbed trailer / ext.<br>15.2 m + 2 steering axles |
| Chassis number          | ***WKVDAS00400062336                                    |
| 1st Registration Date   | 10-10-2014                                              |
| Country of registration | TR                                                      |
| Dimensions              | 1410x255x365 cm                                         |

## POWERTRAIN

ABS 

## CHASSIS

|                  |          |
|------------------|----------|
| Empty weight     | 13880 kg |
| Gross weight     | 58000 kg |
| Chassis height   | 90 cm    |
| Kingpin height   | 130 cm   |
| Kingpin diameter | 2 inches |

## TYRES

|                  |             |
|------------------|-------------|
| Tyre size axle 1 | 245/70R17.5 |
| Tyre size axle 2 | 245/70R17.5 |
| Tyre size axle 3 | 245/70R17.5 |
| Tyre size axle 4 | 245/70R17.5 |



## ADDITIONAL INFO

3 UNITS AVAILABLE // ONLY COPIES OF REG. DOCUMENTS // 4-axle extendable semi-lowbed trailer with hydraulic ramps, 2 Steering rear axles, Lift axle (front), Air suspension, Drum brakes, SAF axles, Dual tyres 245/70R17.5, ABS // Max. gross weight 58000 kg, Max. kingpin load 18000 kg, Max. weight per axle 10000 kg // DIMENSIONS // Min. load bed length 924 cm, Max. load bed length 1524 cm (extends 600 cm), Load bed height 90 cm, Min. load bed width 255 cm, Max. load bed width 375 cm (2 x 60 cm extensions), Gooseneck length 390 cm (320 cm with toolbox), Gooseneck loading height 145 cm, Headboard height 60 cm, Kingpin height 130 cm, 2-inch kingpin, Ramp length 395 cm, Adjustable ramp width, Total shipment dimensions (not extended): 1410x255x365 cm

## AXLES

|                       |                |
|-----------------------|----------------|
| Number of axles       | 4              |
| Brand axles           | Saf            |
| Drum brake            | ✓              |
| Suspension axle 1     | Air suspension |
| Suspension axle 2     | Air suspension |
| Suspension axle 3     | Air suspension |
| Suspension axle 4     | Air suspension |
| Steering axle, Axle 3 | ✓              |
| Steering axle, Axle 4 | ✓              |

## EXCEPTIONAL TRANSPORT

|                     |                                          |
|---------------------|------------------------------------------|
| Adjustable ramps    | ✓                                        |
| Extendable          | ✓                                        |
| Max. length         | 1524 cm                                  |
| Extendable width    | ✓                                        |
| Max width           | 375 cm (2 x 60 cm extensions)            |
| Ramp length         | 395 cm                                   |
| Load bed length     | Min. 924 cm, max. 1524 cm (extends 600 c |
| Goose neck length   | 390 cm (320 cm with toolbox)             |
| Axle plateau length | 924 cm                                   |
| Hydraulic ramps     | ✓                                        |