Nooteboom

4-axle semi-lowbed trailer 69 t / extendable 12 m + ramps

GENERAL

ID number	O000115
Brand	Nooteboom
Type	4-axle semi-lowbed trailer 69 t / extendable 12 m + ramps
Chassis number	***XMR0SD00F0000115
1st Registration Date	01-01-2015
Country of registration	UK
Dimensions	1390x275x320 cm

POWERTRAIN

ABS	✔

CHASSIS

Gross weight	Design weight: 69000 kg, MGW 89700 kg at 12 mpg
Chassis height	85 cm
Kingpin diameter	2 inches
Kingpin height	120 cm

TYRES

Tyre size axle 1	245/70R17.5
Tyre size axle 2	245/70R17.5
Tyre size axle 3	245/70R17.5
Tyre size axle 4	245/70R17.5

ADDITIONAL INFO

4-axle extendable semi-lowbed trailer, Air suspension, 2 Steering rear axles (passive), Front axle lift, SAF axles, Drum brakes, Dual tyres 245/70R17.5, Hydraulic ramps // DIMENSIONS // Load bed length min. 920 cm, Max. load bed length 1220 cm (extends 300 cm), Load bed width 275 cm (extendable to 319, 22 cm on each side), Load bed height 85 cm, Gooseneck length 390 cm, Gooseneck floor height 165 cm, Kingpin height 120 cm, Kingpin diameter 2 inches, Ramp length 375 cm, Ramp width 87 cm each, Adjustable ramp position // WEIGHTS // Design gross weight 69000 kg, Max. gross weight under UK special types provision: 89700 kg at 12 mph, 78890 kg at 20-25 mph, 73640 kg at 30 mph, 71570 kg at 35 mph, 70800 kg at 40 mph, Max. kingpin load 32500 kg - 26000 kg, Shipment dimensions 1390x275x320 cm

AXLES

Number of axles	4
Brand axles	Saf
Suspension axle 1	Air suspension
Suspension axle 2	Air suspension
Suspension axle 3	Air suspension
Suspension axle 4	Air suspension
Lift axle Axle 1	✔
Steering axle, Axle 3	✔
Steering axle, Axle 4	✔

SUPERSTRUCTURE

Make superstructure	Nooteboom
Floor height	85 cm
Platform	✔
Dimensions superstructure	920x275 cm

EXCEPTIONAL TRANSPORT

2-delige rijplaten	✔
Adjustable ramps	✔
Extendable	✔
Max. length	1220 cm
Extendable width	✔
Max width	319 cm
Ramp length	375 cm
Load bed length	920 cm
Goose neck length	390 cm
Axle plateau length	920 cm
Hydraulic ramps	✔